

Add
AZ

090701 090845 090850 090855 090900 090905 090910 090915 090920 090925 090930 090935 090940 090945 090950 090955 091000 091005 091010 091015 091020 091025 091030 091035 091040 091045 091050 091055 091100 091105 091110 091115 091120 091125 091130 091135 091140 091145 091150 091155 091200 091205 091210 091215 091220 091225 091230 091235 091240 091245 091250 091255 091300 091305 091310 091315 091320 091325 091330 091335 091340 091345 091350 091355 091400 091405 091410 091415 091420 091425 091430 091435 091440 091445 091450 091455 091500 091505 091510 091515 091520 091525 091530 091535 091540 091545 091550 091555 091600 091605 091610 091615 091620 091625 091630 091635 091640 091645 091650 091655 091700 091705 091710 091715 091720 091725 091730 091735 091740 091745 091750 091755 091800 091805 091810 091815 091820 091825 091830 091835 091840 091845 091850 091855 091900 091905 091910 091915 091920 091925 091930 091935 091940 091945 091950 091955 092000 092005 092010 092015 092020 092025 092030 092035 092040 092045 092050 092055 092100 092105 092110 092115 092120 092125 092130 092135 092140 092145 092150 092155 092200 092205 092210 092215 092220 092225 092230 092235 092240 092245 092250 092255 092300 092305 092310 092315 092320 092325 092330 092335 092340 092345 092350 092355 092400 092405 092410 092415 092420 092425 092430 092435 092440 092445 092450 092455 092500 092505 092510 092515 092520 092525 092530 092535 092540 092545 092550 092555 092600 092605 092610 092615 092620 092625 092630 092635 092640 092645 092650 092655 092700 092705 092710 092715 092720 092725 092730 092735 092740 092745 092750 092755 092800 092805 092810 092815 092820 092825 092830 092835 092840 092845 092850 092855 092900 092905 092910 092915 092920 092925 092930 092935 092940 092945 092950 092955 093000 093005 093010 093015 093020 093025 093030 093035 093040 093045 093050 093055 093100 093105 093110 093115 093120 093125 093130 093135 093140 093145 093150 093155 093200 093205 093210 093215 093220 093225 093230 093235 093240 093245 093250 093255 093300 093305 093310 093315 093320 093325 093330 093335 093340 093345 093350 093355 093400 093405 093410 093415 093420 093425 093430 093435 093440 093445 093450 093455 093500 093505 093510 093515 093520 093525 093530 093535 093540 093545 093550 093555 093600 093605 093610 093615 093620 093625 093630 093635 093640 093645 093650 093655 093700 093705 093710 093715 093720 093725 093730 093735 093740 093745 093750 093755 093800 093805 093810 093815 093820 093825 093830 093835 093840 093845 093850 093855 093900 093905 093910 093915 093920 093925 093930 093935 093940 093945 093950 093955 094000 094005 094010 094015 094020 094025 094030 094035 094040 094045 094050 094055 094100 094105 094110 094115 094120 094125 094130 094135 094140 094145 094150 094155 094200 094205 094210 094215 094220 094225 094230 094235 094240 094245 094250 094255 094300 094305 094310 094315 094320 094325 094330 094335 094340 094345 094350 094355 094400 094405 094410 094415 094420 094425 094430 094435 094440 094445 094450 094455 094500 094505 094510 094515 094520 094525 094530 094535 094540 094545 094550 094555 094600 094605 094610 094615 094620 094625 094630 094635 094640 094645 094650 094655 094700 094705 094710 094715 094720 094725 094730 094735 094740 094745 094750 094755 094800 094805 094810 094815 094820 094825 094830 094835 094840 094845 094850 094855 094900 094905 094910 094915 094920 094925 094930 094935 094940 094945 094950 094955 095000 095005 095010 095015 095020 095025 095030 095035 095040 095045 095050 095055 095100 095105 095110 095115 095120 095125 095130 095135 095140 095145 095150 095155 095200 095205 095210 095215 095220 095225 095230 095235 095240 095245 095250 095255 095300 095305 095310 095315 095320 095325 095330 095335 095340 095345 095350 095355 095400 095405 095410 095415 095420 095425 095430 095435 095440 095445 095450 095455 095500 095505 095510 095515 095520 095525 095530 095535 095540 095545 095550 095555 095600 095605 095610 095615 095620 095625 095630 095635 095640 095645 095650 095655 095700 095705 095710 095715 095720

- the at least one entity is arranged on and/or in a substrate (60), said substrate (60) preferably being arranged on a support (61) and having a refraction-index which is different from the one of an at least one component adjacent to the substrate (60),
- the at least one entity is scanned with a measuring volume (70) using at least one device being confocal or configured for multi-photon-excitation said device consisting of a radiation source (10) and at least one objective (32), thereby receiving measuring values of optical parameters which are processed by means of signal processing for characterization of the at least one entity,
- the at least one entity substantially maintains its position with respect to the substrate (60) or the support (61) or both for the duration of the obtaining the measuring values,
- before and/or during the scanning process an auxiliary focus (71) is generated by means of at least one second radiation source (11) and an objective (34), said auxiliary focus (71) is at least partly arranged on the interface (62) between substrate (60) and adjacent component or on another interface (62) having a defined spacial relation to said entity,
- a retroreflection from the auxiliary focus (71) is detected by a confocal arranged detector (21) or a plurality of detectors (21,22) being arranged in front of and/or behind the image-plane and along the optical axis of the optic (34) generating the auxiliary focus (71), said retroreflection is used for measuring the position of the interface (62) and, thus, for indirectly positioning the measuring volume (70), and
- the position of the auxiliary focus (71) relative to the measuring volume (70) is adjusted or adjustable in a defined manner.

2. Method according to claim 1 characterized in that the auxiliary focus (71) is generated by means of the same radiation source (10) and/or the same objective (32) which also serves for generating the measuring volume (70).
3. Method according to claim 1 or 2 characterized in that the extent of the confocal detected volume of the auxiliary focus (71), in particular in direction of the respective optical axes of the objectives (32,34) is smaller than the extent of the measuring volume (70).
4. Method according to claim 3 characterized in that the auxiliary focus (71) for obtaining a smaller extent of the confocal detected volume of the auxiliary focus (71) is generated by an optic (34) having a numeric aperture which is larger than the numeric aperture of the optic (32) used for generating the measuring volume (70).
5. Method according to claim 3 characterized in that for obtaining the small extent of the confocal detected volume of the auxiliary focus (71) the smaller part of the numerical aperture of a common optic or the respective optics (32,34) is used for generating the measuring volume (70) than for generating the auxiliary focus (71).
6. Method according to claim 3 characterized in that for obtaining the small extent of the confocal detected volume of the auxiliary focus (71) a confocal arranged diaphragm (51) is used at the detection of the auxiliary focus (71), said diaphragm (51) having a smaller opening than a confocal arranged diaphragm (50) used at the detection of the measuring volume (70).
7. Method according to claim 1 characterized in that for indirectly positioning the measuring volume (70) the position of the auxiliary focus (71) relative to the interface (62) is moved preferably periodically substantially along the optical axis of the optic (34) generating the auxiliary focus

0966845-09071
T.02.060-54889860

(71), the intensity of the retroreflection in dependence on the movement of the detector (21) is registered and the position of the auxiliary focus (71) is readjusted in a manner that the intensity of the retroreflection reaches its maximum.

8. Method according to claim 1 characterized in that for indirectly positioning the measuring volume (70) the position of the auxiliary focus (71) relative to the interface (72) is moved both, laterally to the optical axis of the optic (34) generating the auxiliary focus (71) and axial.
9. Method according to claim 7 or 8 characterized in that the amplitude of the preferably periodical movement of the auxiliary focus (71) is smaller than or equal to the axial extent of the measuring volume (70).
10. Method according to claim 1 characterized in that the intensity of the retroreflection is detected by means of at least two detectors (21,22) and the position of the interface (62) is determined by means of the distribution of the intensities detected by the detectors (21,22).
11. Method according to claim 1 whereby the scatter-light-intensity and/or the scatter-light-intensity in dependence on the polarization and/or the fluorescence-intensity at at least one wavelength and/or the fluorescence-intensity in dependence on the polarization and/or the fluorescence-durability and/or molecular luminosity and/or Raman-scattering and/or luminescence are detected as optical parameters.
12. Method according to claim 1 whereby mineral or organic substrates (60) in particular polymeric gels, polymeric particles built up from inorganic materials, vesicular structures, cells, bacteria and virus are used.
13. Method according to claim 1 whereby molecules, molecule-complexes, polymers, polymeric particles, particles built up from inorganic material, vesicular structures, cells, bacteria and virus are used as entities.

09868845.090701

14. Method according to claim 1 whereby entities and/or substrates (60) selected by means of the optical parameters are separated during or after the scanning process from the other entities and/or substrates (60).
15. Method according to claim 1 for use in the research of active ingredients, in the functional analysis of combinatoric-chemical or combinatoric-biological synthesis-products, in the functional genom-analysis, in the evolutive biotechnology, in the diagnostics, in the proteom-analysis or the investigation of material.
16. Apparatus for performing the method according to claim 1 comprising
- at least one first radiation source (10) as well as at least one device being confocal or configured for multi-photon-excitation said device comprising an objective (32) and at least one first detector (20) for detecting measuring values from the measuring volume (70),
 - at least one second radiation source (11) as well as at least one further device comprising an objective (34) and at least one second detector (21) for detecting a retroreflection from an auxiliary focus (71) whereby a confocal arranged second detector (21) or a plurality of detectors (21,22) being arranged in front of and/or behind the image plane and along the optical axis of the optic (34) generating the auxiliary focus (71) are used,
 - at least one device for positioning measuring volume (70) and auxiliary focus (71) relative to a substrate (60), and
 - a device for variably positioning the auxiliary focus (71) relative to the measuring volume (70).
17. Apparatus for performing the method according to claim 1 comprising
- at least one first radiation source (10) as well as at least one device being confocal or configured for multi-photon-excitation said device comprising an objective (32) and at least one first detector (20) for detecting measuring values from a measuring volume (70),

09868845-090701

- at least one second radiation source (11) as well as at least one further device comprising an objective (34) in at least one second detector (21) for detecting a retroreflection from an auxiliary focus (71) whereby a confocal arranged second detector (21) or a plurality of detectors (21,22) arranged in front of and/or behind the image-plane and along the optical axis of the objective (34) generating the auxiliary focus (61) is used,
 - at least one device for positioning of measuring volume (70) and auxiliary focus (71) relative to the substrate (60),
 - whereby the auxiliary focus (71) is adjusted relative to the measuring volume (70) in a defined manner.
18. Apparatus according to claim 16 characterized in that the device for positioning the measuring volume (70) and the auxiliary focus (71) relative to the substrate (60) comprises means for positioning the auxiliary focus (71) relative to the measuring volume (70).
19. Apparatus according to one of the claims 16 or 18 characterized in that the same first radiation source (10) and/or objective (32) is used for generation of the measuring volume (70) and the auxiliary focus (71).
20. Apparatus according to claim 16 characterized in that the device for positioning the auxiliary focus (71) relative to the measuring volume (70) comprises means for adjusting the relative position of the objectives (32,34).
21. Apparatus according to claim 16 characterized in that the device for positioning the auxiliary focus (71) relative to the measuring volume (70) comprises means for variation of the convergence of those ray bundles being focussed by the respective objective (32,34) for generating the auxiliary focus (71) and the measuring volume (70).

0966845-090701

22. Use of the apparatus according to claim 16 in the research of active ingredients, the functional analysis of combinatoric chemical or combinatoric-biological synthesis products, the functional genom-analyses, the evolutive biotechnology, the diagnostics, the proteom-analyses or in the investigation of material.

09868845-090701
T02060-54889860